

## Modulux 10 Watt high CRI Integrated LED track head

A versatile dimmable LED track lighting solution, for discriminating art galleries, retail stores, restaurants and residences.

Available in six different colour temperatures to suit any environment, including 2400K and dim-to-warm for intimate lighting in hospitality settings.

Strict colour binning control ensures that the light from each of our Integrated LED track heads will look the same from one to the next.

### Optical adaptability

The Modulux features optical lenses which can be changed in the field (from spot lighting to flood lighting). Alternate lenses are available in 15, 25, 40 and 60 degrees (sold separately). Simply unscrew the baffle and change the lens.

Comes with H-type track connector (Halo-compatible). Other types (J and L) available upon request.

Dimmable with most common dimmers. cETLus safety certified.

### How to order:

#### MX - CCT - BEAM - FINISH - CONNECTOR

Examples: MX-30K-40-WH-H (Modulux 3000K 40 degree beam, white finish, with Halo track connector)

MX-DTW-25-BK-J (Modulux Dim To Warm 25 degree beam, black finish, with Juno track connector)



Available Colour Temperatures	CRI	Available Finishes	LED Type	Dimmable	Dimensions	Beam Angles
3000K-2200K (Dim to Warm) 2400K 2700K 3000K 3500K 4000K	90+ 90+ 95+ 95+ 95+ 95+	White, Black	COB	Yes (AC/Triac) MLV or ELV	(H total) 5.6" / 143 mm (L) 4.25" / 108 mm (H) 2.35" / 60 mm (D) 2.35" / 60 mm	15, 25, 40, 60 degrees

Voltage Input	Power use	Lumen Output	Power Factor	Operating Temperature	Weight
110V-120 AC at 60 Hz.	10 watts	780 lm. 3000K 830 lm. 4000K	0.9	-20C to 45C	.32 kg / 0.7 lb.

Perfect for offices, galleries, retail, residential and hospitality environments.