

Lumicrest LED lights bring energy savings, bright clear light, and long life reliability.

This unique downlight is 4 inches in diameter. A switch on the back allows you to choose the colour temperature (2700K, 3000K, 4000K) on the spot- one light fits all. Its integrated LEDs emit through a frosted diffuser to create smooth coverage.

The result is a field of light which is surprisingly bright and even.



Get the Lumicrest Advantages

The light can be installed with a new-construction mounting plate or retrofit into the ceiling by using a round hole in the drywall. The spring loaded clips grip the back side of the drywall, holding the light securely in place.

Each light comes with an external LED driver (transformer) in a certified enclosure with a barrel connector that plugs into the light.

Perfect for galleries, museums, hotels, resorts, offices, retail environments and residences.

Item	Dimensions (mm)	LED Type	Dimmable	Colour Temperature	Lens Angles
778 dl-27-30-40-4in 779 -dl-27-30-40-6in	4inch: 27(H) *102(Diam) 6inch: 27(H) *170(Diam) Height includes Switch	Array	Yes	2700k warm white 3000k clean white 4000k natural white	NA
Voltage Input	Power use	Lumen Output	Working Temperature	Weight	
90V-130V AC at 60 hz.	4inch: 9 watts 6inch: 12 watts	4inch: 600 lm 6inch: 1100 lm	-20C to 40C	4inch: 0.315 kg 6inch: 0.415 kg	

Contact us today to learn more about how you can take advantage of the many benefits of Lumicrest LED technology. 1.866.609.0282 info@lumicrest.com