

Features and Benefits:

- Quick and easy installation
- Tiltable spotlight (20 degree tilt)
- 95 CRI for full spectrum colour rendering
- Uses only 6 watts of power
- Emits no UV or IR rays, contains no mercury
- cETL listed for USA and Canada
- Generates bright, focused soft white light
- No heat emitted in the beam
- Dimmable, for maximum lighting control
- Attractive, clean design
- IC rated for insulated ceilings
- Damp rated for damp locations



Installation:

- cut 3" (75mm) hole in drywall
- connect driver enclosure to light (using low-voltage wires & barrel connectors (included))
- connect 120 VAC to driver within enclosure
- put driver enclosure through ceiling hole and install light into hole using spring-clips on rear of light



Item	External Dimensions		Power	Colour Temperature	Lumens
722-dl_gim-ww25	Light: 88 mm outer ring diameter.		6 watts	2700k warm white	450 lumens
723-dl_gim-clw25	70 mm main-body diameter.			3000k clean white	475 lumens
734-dl_gim-clw40	37mm total depth			3000k clean white	475 lumens
Driver enclosure: 103mm x 62mm x 40mm					
Voltage Input	Dimmable	CRI	Working Temperature		Certifications
110V-120 AC at 60 hz.	Yes, common Triac dimmers	95 + CREE COB LED	-20C to 40C		cETL

Contact us today to learn more about how you can take advantage of the many benefits of Lumicrest LED technology. 1.866.609.0282 info@lumicrest.com